HYCON HRD28X ROCK DRILL

PRODUCT FEATURES

The HYCON HRD28X is a high performing handheld rock drill designed for the toughest drilling applications in granite and concrete up to 6 meters of drilling depths.

Using standard integral drill steel with air-flushing from an <u>external</u> compressor combined with a high performing hydraulic impact and rotation unit makes the HRD28X a lighter, powerful and efficient rock drill.

The HRD28X rock drill is ideal for anchoring holes as well as blast- or splitting holes measuring between 25-50 mm when you need to drill deeper with maximum air flushing.

HYDRAULIC ROCK DRILL HRD28X

Item no. HRD28X	1010301
Technical information	
Dimensions: LxW, mm/ Weight, kg	708x406/27,5
Oil flow, l.p.m.	30
Working pressure, bar	130
Max. pressure, bar	172
Drill steel shank size, mm hex	22x108



Combined with a compressor of your choice, it is made for underwater drilling, making it the professional divers rock drill choice no. 1.

Blending the hydraulic and pneumatic advantages in one product, you get a rock drill that can drill anywhere, go deeper and still light enough to use for many hours.

Simply connect it to one of HYCONs compact hydraulic power packs and a compressor – and start drilling.

Consult one of our salespersons for recommendations for deeper and wider drilling

Rotation (Clockwise), r.p.m.	320
Blow frequency, Hz	40
Noise level LWA dB	105
Min. Required Air Flushing, m3/h	10
Vibration level (3 axis) m/s2	13
Air connection	1/4" BSP Female Thread







Contact us for more information: hycon@hycon.dk / +45 96 47 52 00

THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS • CORE DRILLS • POST DRIVERS • PICK HAMMER • LIGHT & HEAVY DUTY BREAKERS SUBMERSIBLE PUMPS • ROCK DRILLS • UNDERWATER EQUIPMENT • GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S Juelstrupparken 11 DK-9530 Støvring

Tel +45 9647 5200 www.hycon.dk KWHydraulik Aggregate und Werkzeuge www.kw-hydraulik.de info@kw-hydraulik.de +49 3675 421980

DISTRIBUTOR: